

High flexible round stranded copper cable

Article no.		Technical data			
Uncoated	Tinned	Area mm²	Dimensions mm		Weight kg/100m
			No. of threds and diameter	Outer dia.	
CUBL 1	CUFÖ 1	1	512 x 0,05	1,5	1
CUBL 1,5	CUFÖ 1,5	1,5	392 x 0,07	1,9	1,7
CUBL 2,5	CUFÖ 2,5	2,5	651 x 0,07	2,4	2,7
CUBL 4	CUFÖ 4	4	1036 x 0,07	3,1	4
CUBL 6	CUFÖ 6	6	1561 x 0,07	4	6
CUBL 8	CUFÖ 8	8	2100 x 0,07	4,2	8
CUBL 10	CUFÖ 10	10	2604 x 0,07	4,5	10
CUBL 16	CUFÖ 16	16	4200 x 0,07	5,7	16
CUBL 25	CUFÖ 26	25	3192 x 0,10	7,5	25
CUBL 35	CUFÖ 35	35	4480 x 0,10	9	35
CUBL 50	CUFÖ 50	50	6383 x 0,10	11	50
CUBL 70	CUFÖ 70	70	8918 x 0,10	13	70
CUBL 95	CUFÖ 95	95	12100 x 0,10	15	100
CUBL120	CUFÖ120	120	15300 x 0,10	17	127
CUBL150	CUFÖ150	150	19152 x 0,10	19	158
CUBL185	CUFÖ185	185	23580 x 0,10	21	194
CUBL240	CUFÖ240	240	30600 x 0,10	23,5	247
CUBL300	CUFÖ300	300	38200 x 0,10	27,5	310
CUBL400	CUFÖ400	400	50960 x 0,10	33	410
CUBL500	CUFÖ500	500	64288 x 0,10	38	508
CUBL600	CUFÖ600	600	76832 x 0,10	43	600
CUBL750	CUFÖ750	750	95648 x 0,10	46	750
CUBL850	CUFÖ850	850	108976 x 0,10	48	850
CUBL1000	CUFÖ1000	1000	128576 x 0,10	54	1010



Technical data

Material
Annealed Cu-ETP
uncoated or tinned version

Supplied by meter or as customized
connections

Produced according to
DIN EN 13602

Other areas and dimensions upon
request

