

High flexible round stranded copper cable

Article no.		Technical data			
Uncoated	Tinned	Area mm²	Dimensions mm		Weight kg/100m
			No. of threds and diameter	Outer dia.	
CUBL001	CUFÖ001	1	512 x 0,05	1,5	1
CUBL001,5	CUFÖ001,5	1,5	392 x 0,07	1,9	1,7
CUBL002,5	CUFÖ002,5	2,5	651 x 0,07	2,4	2,7
CUBL004	CUFÖ004	4	1036 x 0,07	3,1	4
CUBL006	CUFÖ006	6	1561 x 0,07	4	6
CUBL008	CUFÖ008	8	2100 x 0,07	4,2	8
CUBL010	CUFÖ010	10	2604 x 0,07	4,5	10
CUBL016	CUFÖ016	16	4200 x 0,07	5,7	16
CUBL025	CUFÖ025	25	3192 x 0,10	7,5	25
CUBL035	CUFÖ035	35	4480 x 0,10	9	35
CUBL050	CUFÖ050	50	6383 x 0,10	11	50
CUBL070	CUFÖ070	70	8918 x 0,10	13	70
CUBL095	CUFÖ095	95	12100 x 0,10	15	100
CUBL120	CUFÖ120	120	15300 x 0,10	17	127
CUBL150	CUFÖ150	150	19152 x 0,10	19	158
CUBL185	CUFÖ185	185	23580 x 0,10	21	194
CUBL240	CUFÖ240	240	30600 x 0,10	23,5	247
CUBL300	CUFÖ300	300	38200 x 0,10	27,5	310
CUBL400	CUFÖ400	400	50960 x 0,10	33	410
CUBL500	CUFÖ500	500	64288 x 0,10	38	508
CUBL600	CUFÖ600	600	76832 x 0,10	43	600
CUBL750	CUFÖ750	750	95648 x 0,10	46	750
CUBL850	CUFÖ850	850	108976 x 0,10	48	850
CUBL1000	CUFÖ1000	1000	128576 x 0,10	54	1010



Technical data

Material
Annealed Cu-ETP
uncoated or tinned version

Supplied by meter or as customized connections

Produced according to
DIN EN 13602

Other areas and dimensions upon request

