

High flexible round stranded copper cable

Article no.		Technical data			
Uncoated	Tinned	Area mm²	Dimensions mm		Weight kg/100m
			No. of threds and diameter	Outer dia.	
CUBL0001	CUFÖ0001	1	512 x 0,05	1,5	1
CUBL0001,5	CUFÖ0001,5	1,5	392 x 0,07	1,9	1,7
CUBL0002,5	CUFÖ0002,5	2,5	651 x 0,07	2,4	2,7
CUBL0004	CUFÖ0004	4	1036 x 0,07	3,1	4
CUBL0006	CUFÖ0006	6	1561 x 0,07	4	6
CUBL0008	CUFÖ0008	8	2100 x 0,07	4,2	8
CUBL0010	CUFÖ0010	10	2604 x 0,07	4,5	10
CUBL0016	CUFÖ0016	16	4200 x 0,07	5,7	16
CUBL0025	CUFÖ0025	25	3192 x 0,10	7,5	25
CUBL0035	CUFÖ0035	35	4480 x 0,10	9	35
CUBL0050	CUFÖ0050	50	6383 x 0,10	11	50
CUBL0070	CUFÖ0070	70	8918 x 0,10	13	70
CUBL0095	CUFÖ0095	95	12100 x 0,10	15	100
CUBL0120	CUFÖ0120	120	15300 x 0,10	17	127
CUBL0150	CUFÖ0150	150	19152 x 0,10	19	158
CUBL0185	CUFÖ0185	185	23580 x 0,10	21	194
CUBL0240	CUFÖ0240	240	30600 x 0,10	23,5	247
CUBL0300	CUFÖ0300	300	38200 x 0,10	27,5	310
CUBL0400	CUFÖ0400	400	50960 x 0,10	33	410
CUBL0500	CUFÖ0500	500	64288 x 0,10	38	508
CUBL0600	CUFÖ0600	600	76832 x 0,10	43	600
CUBL0750	CUFÖ0750	750	95648 x 0,10	46	750
CUBL0850	CUFÖ0850	850	108976 x 0,10	48	850
CUBL1000	CUFÖ1000	1000	128576 x 0,10	54	1010



Technical data

Material
Annealed Cu-ETP
uncoated or tinned version

Supplied by meter or as customized connections

Produced according to
DIN EN 13602

Other areas and dimensions upon request

